

Features

- **Numeric Control**
- **Linear Type**
- **Single O/P**
- **Very Stable & Reliable**
- Fully variable
- Complete Output Protection
- Automatic C/V & C/C
- 2 LED DPMs for display of V & I (4 Digits)
- Live Control of O/P Voltage in O/P Off Position (O/P Pause Function).



Specifications :

RATING	:	O/P VOLTAGE = 0 ~ 30 V O/P CURRENT = 0 ~ 5 A
DISPLAY	:	TWO 4 Digits L.E.D. DPMs, FOR 'V' & 'I'
Display Accuracy	:	V : ± (0.2% + 5 Digits) & I : ± (0.5% + 5 Digits)
LOAD REGULATION	:	CV : ≤ 0.01% + 3 mV & CC : ≤ 0.2% + 3 mA
LINE REGULATION	:	CV : ≤ 0.01% + 1 mV & CC : ≤ 0.2% + 1 mA
RIPPLE & NOISE	:	CV : ≤ 0.5 mV _{rms} & CC : ≤ 3 mA _{rms}
ENVIRONMENTAL	:	0 ~ + 40 °C, R.H. < 90%.
OPERATING VOLTAGE	:	220 ~ 240 V AC, 50 Hz
FEATURES	:	Full Numeric Controls with Up/Down, Lock Etc.
PROTECTION	:	C.C., Short Circuit, With Current Limiting
DIMENSION AND WEIGHT	:	130 (W) x 150 (H) x 240 (D) mm, About 2 Kgs.

* All Specifications & appearances are subject to change without prior notice

