

Features

- 3 5/6 Digits (6000 Counts) with backlight
- **600 μ A to 1000 A**
- μ A Ranges for In-Circuit Meas
- True RMS, Auto/Manual Ranging
- Cap., Freq., & Temp. Measurements
- Data Hold & Torch
- Continuity & Diode Test
- A.P.O., & Relative Measurements
- Hz / Duty Button for Switching During ACV & ACA Measurement



SPECIFICATIONS

| | | |
|-----------------------------------------------------------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------|
| DC Voltage | Range | 600 mV, 6 V, 60 V, 600 V, 1000 V |
| | Basic Accuracy | \pm (0.5 % reading + 3 digits) |
| AC Voltage (True RMS) | Range | 600 mV, 6 V, 60 V, 600 V, 750 V |
| | Basic Accuracy | \pm (0.8 % rdg. + 5 digits) |
| AC & DC Current (True RMS AC) | Range | 600 μ A / 6000 μ A / 60 A / 600 A / 1000 A μ A Ranges : for In-Circuit Measurement through the Meter. |
| | Basic Accuracy | \pm (0.8 % rdg. + 10 digits) |
| Resistance | Range | 600 Ω , 6 K Ω , 60 K Ω , 600 K Ω , 6 M Ω , 60 M Ω |
| | Basic Accuracy | \pm (0.8% rdg. + 5 digits) |
| Capacitance Test | | 60 nF, 600 nF, 6 μ F, 60 μ F, 600 μ F & 6000 μ F. |
| Frequency Measurement @ | | 10 Hz, 100 Hz, 1 KHz, 10 KHz, 100 KHz & 1 MHz / 20 MHz. |
| Temperature Measurement | | -20 ~ 1,000 $^{\circ}$ C (0 ~ 1,832 $^{\circ}$ F) |
| Diode Test, Continuity Test, Data Hold & Relative Measurement Facility | | Provided |
| Accessories Supplied | | Test Leads - Pair, Carrying Pouch, Temp., Probe, User Manual & Battery (Installed / Kept Aside). |
| Dimension & Weight | | 280 x 70 x 45 mm & Approx. 300 gms. (Incl. Batt.). |
| @ USE OF Hz / Duty Button Recommended when measuring AC Mains Freq | | |

* All Specifications & appearances are subject to change without prior notice

