

## Features

- 3 1/2 Digits (2000 Counts)
- Manual Ranging
- True RMS
- Continuity test, Diode test
- Data hold, Torch, Live & Tr. (hFE) Test
- Capacitance test & Low Batt., Indicator
- Superior Quality & Reliable Instrument
- 200  $\mu$ A & 200 M $\Omega$  Ranges



### SPECIFICATIONS

<b>DC Voltage</b>	Range	200 mV, 2 V, 20 V, 200 V, 1000 V	
	Basic Accuracy	$\pm$ (0.5 % rdg + 4 digits)	Input Imp. : About 10 M $\Omega$
<b>AC voltage</b>	Range	2 V, 20 V, 200 V, 750 V	
	Basic Accuracy	$\pm$ (0.8 % rdg + 4 digits)	Input Imp. : About 10 M $\Omega$
<b>DC current</b>	Range	200 $\mu$ A, 2 mA, 20 mA, 200 mA, 10 A	
	Basic Accuracy	$\pm$ (0.8 % rdg + 5 digits)	
<b>AC current</b>	Range	200 mA, 10 A	
	Basic Accuracy	$\pm$ (2 % rdg + 3 digits)	
<b>Resistance</b>	Range	200 $\Omega$ , 2 K $\Omega$ , 20 K $\Omega$ , 200 K $\Omega$ , 2 M $\Omega$ , 20 M $\Omega$ , 200 M $\Omega$	
	Basic Accuracy	$\pm$ (1 % rdg + 25 digits)	
<b>Capacitance</b>	Range	20 nF, 2 $\mu$ F, 200 $\mu$ F	
	Accuracy	$\pm$ (2.5 % rdg + 20 digits)	
<b>ACV &amp; ACA Frequency Response</b>		40 ~ 1 KHz	
<b>Continuity Test, Diode &amp; Tr. (hFE) Test</b>		Provided	
<b>Other Facilities / Features</b>		Auto Power Off, Low Batt., Ind., 9 V Batt., Oper.	
<b>Accessories Supplied</b>		Test Leads, User Manual & Battery (Installed / Kept Aside).	
<b>Dimension &amp; Weight</b>		167 x 81 x 43 mm & Approx. 167 gms. (W/o. Batt.)	

\* All Specifications & appearances are subject to change without prior notice

