

## Features

- 3 5/6 Digits (6000 Counts)
- 60 / 600 A / 1000 A AC/DC
- 2000 V AC/DC (Solar)  
Meas. Using Test Socket Provided (Only)
- True RMS, Auto Ranging
- Cap., Freq., & Temp. Measurements
- In Rush Current & V.F.C.
- Data Hold, B/L & Torch
- Continuity & Diode Test
- A.P.O., NCV & Live Wire Test

**DC 2000V**  
**AC 2000V**



### SPECIFICATIONS

<b>DC Voltage</b>	Range	600 mV, 6 V, 60 V, 600 V, <b>2000 V #</b>
	Basic Accuracy	± (0.5 % reading + 7 digits)
<b>AC Voltage (True RMS)</b>	Range	6 V, 60 V, 600 V, <b>2000 V #</b>
	Basic Accuracy	± (1 % rdg. + 10 digits)
<b>AC Current &amp; DC Current</b>	Range	60 A / 600 A / 1000 A ( <b>True RMS ACA</b> )
	Accuracy	± (4 % rdg. + 10 digits)
<b>Resistance</b>	Range	600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 60 M Ω
	Basic Accuracy	± (1% rdg. + 5 digits)
<b>Capacitance Test (Auto Ranging)</b>		1 nF, 10 nF, 100 nF, 1 μF, 10 μF, 100 μF, 1 mF & 10 mF.
<b>Frequency / D. Cycle (Auto Ranging)</b>		10 Hz ~ 10 MHz. <b>Protection Upto 250 V ONLY.</b>
<b>Temperature Measurement</b>		-20 ~ 1000 °C (-4 ~ 1832 °F).
<b>Other Facilities / Features</b>		NCV & Live Wire Test, Diode Test, Continuity Test, Back Light, Torch, Auto Power Off, Low Batt. Indication, Data Hold, REL, In Rush Current & V.F.C.
<b>Accessories Supplied</b>		Test Leads - Pair, Temp., Probe, H.V. Test Socket, Carrying Pouch, User Manual & <u>Battery (Installed / Kept A - OPTIONAL.</u>
<b>Dimension &amp; Weight</b>		230 x 75 x 40 mm & Approx. 315 gms. (Incl. Batt.).

\* All Specifications & appearances are subject to change without prior notice

