

## Features

- 3 5/6 Digits (6000 Counts)
- True RMS, Auto Ranging
- 6 / 60 / 600 / 1000 A AC
- 1000/750 V DC/AC
- Low Imp. ACV Meas. (TRMS)
- Data Hold, B/L & Torch
- Continuity & Diode Test
- A.P.O., NCV & Live Wire Test
- Heavy Duty



### SPECIFICATIONS

|  |   |  |
|--|---|--|
| <b>DC Voltage</b>                            | Range   | 600 mV, 6 V, 60 V, 600 V, 1000 V                     |
|  | Basic Accuracy  | ± (0.5% reading + 7 digits)                          |
| <b>AC Voltage (True RMS)</b>                 | Range   | 6 V, 60 V, 600 V, 750 V                              |
|  | Basic Accuracy  | ± (1% rdg. + 10 digits)                              |
| <b>AC Current (True RMS)</b>                 | Range   | 6 A / 60 A / 600 A / 1000 A                          |
|  | Basic Accuracy  | ± (4% rdg. + 10 digits)                              |
| <b>Low impedance AC V Measurement (TRMS)</b> | Range   | 6 V, 60 V, 300 V                                     |
|  | Basic Accuracy  | ± (1% rdg. + 10 digits)    Input impedance : ≤ 3 KΩ. |
| <b>Resistance</b>                            | Range   | 600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 20 M Ω, 60 M Ω |
|  | Basic Accuracy  | ± (1% rdg. + 5 digits)                               |
| <b>Other Facilities / Features</b>           | NCV & Live Wire Test, Diode Test, Continuity Test, Back Light, Torch, Auto Power Off, Low Batt. Indication, Data Hold & Min./Max. |  |
| <b>Accessories Supplied</b>                  | Test Leads, Carrying Pouch, User Manual & Battery - 2 x AAA (Installed / Kept Aside).   |  |
| <b>Dimension &amp; Weight</b>                | 230 x 75 x 40 mm & Approx. 315 gms. (Incl. Batt.).  |  |

\* All Specifications & appearances are subject to change without prior notice

