VAR TECH®
Quality • Reliability • Economy

Digital Clamp Multimeter - V 266

Features

- 3 1/2 Digits (2000 Counts)
- Manual Ranging
- 200 / 1000 A AC
- 1000/750 V DC/AC
- 50 mm Jaw opening
- Simple & Reliable Instrument
- Insulation Tester Optional
- Data Hold Facility

SPECIFICATIONS		
AC Current	Range	200 A & 1000 A
	Accuracy	± (3 % rdg + 5 digits) ≥ 800 A ; Unspecified (for Ref. Only).
	Freq., Response	50 ~ 60 Hz
DC Voltage	Range	1000 V
	Accuracy	± (0.8 % rdg + 1 digit)
AC Voltage	Range	750 V
	Accuracy	± (1.2 % rdg + 4 digits). Freq., Response = 50 ~ 400 Hz.
Resistance	Range	200 Ω & 20 K Ω
	Accuracy	200 Ω range : ± (1% rdg + 3 digits) & 20 K Ω : ± (1% rdg + 1 digits)
Insulation Resistance	Range	20 MΩ & 2000 MΩ
	Accuracy	20 MΩ Range : ± (2 % rdg + 2 digits) 2000 MΩ Range : ≤ 500 MΩ ; ± (4 % rdg + 2 digits) ≥ 500 MΩ ; ± (5 % rdg + 2 digits)
Continuity Test		In 200 Ω Range, When Resistance is below 75 Ω Buzzer will sound
DCV & ACV Input Impedance		9 M Ω
Power source		9 V (6F22)
Accessories Supplied		Test Leads, Operating Manual, Carrying Case & Battery (Installed / Kept Aside).
Dimension & Weight		230 x 70 x 37 mm & Approx. 310 gms. (Incl., Batt.)

** All Specifications & appearances are subject to change without prior notice*

www.var-tech.com