

Features

- 3 ½ Digits (2000 Counts)
- True RMS, Manual Ranging
- 1000 V AC/DC & 20 A AC/DC
- Mains Freq. Meas. In 1000 V AC Range
- Cap., & Freq., Auto range Meas.
- Temperature Measurement
- L.C.D. Back - Light & Torch
- Auto Power Off
- Tr. (Hfe), Diode & Continuity Test
- LIVE WIRE Testing & NCV
- A/V Indication With Holster



SPECIFICATIONS

DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 1000 V
	Basic Accuracy	± (0.5 % rdg + 3 digits)
AC Voltage (TRUE RMS)	Range	2 V, 20 V, 200 V, 1000 V
	Basic Accuracy	± (0.8 % rdg + 5 digits)
DC current	Range	200 µA, 2 mA, 20 mA, 200 mA, 20 A
	Basic Accuracy	± (1.2 % rdg + 8 digits)
AC current (TRUE RMS)	Range	200 mA, 20 A
	Basic Accuracy	± (1.5 % rdg + 15 digits)
Resistance	Range	200 Ω, 2 K Ω, 20 K Ω, 200 K Ω, 2 M Ω, 20 M Ω, 200 M Ω
	Basic Accuracy	± (0.8% rdg + 3 digits)
Capacitance (Auto Ranging)	Range	6 nF, 60 nF, 600 nF, 6 µF, 60 µF, 600 µF, 6 mF & 20 mF
	Basic Accuracy	± (3.5 % rdg + 20 digits)
Frequency (Auto Ranging)	Range	10 Hz, 100 Hz, 1 KHz, 10 KHz, 100 KHz, 1 MHz & 20 MHz
	Basic Accuracy	± (1 % rdg + 10 digits)
Temperature Measurement		- 20 °C ~ + 1000 °C (-4 – 1832) °F
Continuity Test & Diode Test		Provided
Other Facilities / Features		Tr. (Hfe) Test, Data Hold, Auto Power Off, Relative Value Measurement, Low Batt., Indication Etc. 4 x AAA Batt., Oper..
Accessories Supplied		Holster (Installed), Test Leads, User Manual, Temp. Probe, & Battery (Installed / Kept Aside),
Dimension & Weight		186 × 92 × 52 mm & Approx. 395 gms. (With Batt.)

