

Features

- 3 1/2 Digits (2000 Counts)
- Manual Ranging
- True RMS
- Built-In Stand & Holster
- Continuity test, Diode test
- Data hold, Torch, NCV & Tr. (hFE) Test
- With Backlight
- Superior Quality & Reliable Instrument
- 20 μ A & 200 M Ω Ranges



SPECIFICATIONS

DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 600 V
	Basic Accuracy	\pm (0.5 % reading + 5 digits)
	Input impedance	10 M Ω (200 mV Range - > 40 M Ω)
AC Voltage	Range	200 V, 600 V
	Basic Accuracy	\pm (1 % rdg + 6 digits)
	Freq. Response	40 ~ 400 Hz
DC Current	Range	20 μ A, 2 mA, 200 mA, 10 A
	Basic Accuracy	\pm (1 % rdg + 5 digits)
Resistance	Range	200 Ω , 2 K Ω , 20 K Ω , 2 M Ω , 200 M Ω
	Basic Accuracy	\pm (0.8% rdg + 5 digits)
Other Functions / Facilities		Continuity Test, Diode Test, Back-Light, Data Hold, Torch, NCV & Tr. (hFE) Test. Double Fuse Protection (200 mA & 10A).
Power Source		2 Pcs., 1.5 V (AAA) Batteries
Accessories Supplied		Test Leads, User Manual & Battery (Installed / Kept Aside). Holster (Installed).
Dimension & Weight		140 x 72 x 37 mm & Approx. 200 gms. (Including Battery)

* All Specifications & appearances are subject to change without prior notice

