

Features

- 3 5/6 Digits (6000 Counts)
- Auto Ranging / Auto Range Detection
- True RMS
- Primary & Secondary Display
- Input Jack Prompt & Burnt Fuse Prompt
- Auto Ranging Cap., Freq., & Temp., Tests
- A.P.O., NCV, D/H, B/L & Torch
- A/V Continuity & Diode Test with Holster



SPECIFICATIONS

DC Voltage	Range	600 mV, 6 V, 60 V, 600 V
	Basic Accuracy	± (0.5 % rdg + 3 digits)
AC Voltage (True RMS)	Range	6 V, 60 V, 600 V
	Basic Accuracy	± (1 % rdg + 3 digits).
DC Current	Range	600 mA, 6 A, 10 A
	Basic Accuracy	± (1.2 % rdg + 3 digits)
AC Current (True RMS)	Range	600 mA, 6 A, 10 A
	Basic Accuracy	± (1.2 % rdg + 3 digits).
Resistance	Range	600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 60 M Ω
	Basic Accuracy	± (1 % rdg + 5 digits)
Capacitance	Range	6 nF, 60 nF, 600 nF, 6 μF, 60 μF, 600 μF, 6 mF, 60 mF
	Accuracy	± (3.5 % rdg + 20 digits)
Frequency	Range	6 Hz, 60 Hz, 600 Hz, 6 KHz, 60 KHz, 600 KHz, 6 MHz, 10 MHz
	Basic Accuracy	± (1 % rdg + 3 digits)
Temperature	Range	- 40 °C ~ 1000 °C (-40 °F ~ 1832 °F)
Other Facilities / Features	NCV, Torch, ACV Freq., Measurement, A/V Continuity Test, Diode Test, LCD Back Light, Data Hold, Auto Power Off, Low Batt., Ind., Jack & Burnt Fuse Prompt, Intelligent Mode.	
Accessories Supplied	Holster (Installed), Test Leads, User Manual, Battery - 4 x AAA (Installed / Kept Aside) - Optional & Temperature Probe.	
Dimension & Weight	146 x 72 x 50 mm & Approx. 235 gms. (With Batt. & Holster)	

* All Specifications & appearances are subject to change without prior notice

