

Features

- 4 ½ Digits (20000 Counts)
- True RMS, Manual Ranging
- 1000 /750 V DC/AC & 20 A AC/DC
- Full Function protection
- Cap., & Freq., Conductance Meas.
- Temperature Measurement
- L.C.D. Back - Light & Torch
- Auto Power Off & NCV
- Tr. (Hfe), Diode & Continuity Test
- A/V Indication With Holster



SPECIFICATIONS

DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 1000 V
	Basic Accuracy	± (0.1 % rdg + 5 digits)
AC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 750 V True RMS
	Basic Accuracy	± (1 % rdg + 25 digits)
DC current	Range	200 µA, 2000 µA, 20 mA, 200 mA, 20 A
	Basic Accuracy	± (0.5 % rdg + 4 digits)
AC current	Range	20 mA, 200 mA, 20 A True RMS
	Basic Accuracy	± (1.5 % rdg + 15 digits)
Resistance	Range	200 Ω, 2 K Ω, 20 K Ω, 200 K Ω, 2 M Ω, 20 M Ω, 200 M Ω
	Basic Accuracy	± (0.4 % rdg + 10 digits)
Capacitance	Range	20Nf, 200nF, 2 µF, 20 µF, 200 µF, 2 mF
	Accuracy	± (4 % rdg + 50 digits)
Frequency	Range	200 Hz, 2 KHz, 20 KHz, 200 KHz, 2 MHz
	Basic Accuracy	± (0.1 % rdg + 3 digits)
Continuity Test, Transistor (hFE) Test, Diode Test & Conductance Test		Provided
Other Facilities / Features		Data Hold, Torch, Auto Power Off, Fuse Protection - 0.2 A & 20 A, Low Battery Indication.
Accessories Supplied		Holster, Test Leads, User Manual, Battery (Installed / Kept Aside).
Dimension & Weight		186 x 92 x 52 mm & Approx. 400 gms. (Incl. Batt.)

